



Specifications:  
 Current Rating:3.0A AC/DC  
 Voltage Rating:250V AC/DC  
 Contact Resistance:30m ohm. max.  
 Insulation Resistance:5,000M ohm. min.  
 Operating Temperature Range:-40°C ~ +85°C  
 Withstanding Voltage:1,000V AC For One Minute  
 Material and Finish  
 Insulator:High Temp. Plastic (PBT UL 94V-0)  
 Contact:Copper Alloy Nickel Undercoated  
 ,Gold Plated  
 Shell:Metal Iron with nickel plated  
 How To Order  
 5512-XXSA-01-BRJ C6F1  
 Lead Free  
 Screw high:6.0mm  
 BRJ:Hex Screw+Hex Nut  
 01:Gold Plated  
 SA:Stamp Pin Female  
 No.Of Positions

Pos	A	B	C	D	E
15	16.33	24.99	30.81	19.23	2.29
26	24.66	33.32	39.14	27.56	2.29
44	38.38	47.04	53.04	41.28	2.29
62	54.84	63.50	69.32	57.73	2.41

RoHS Compliant

E				<b>DRAWN:</b> CEL KING	<b>GENERAL TOLERANCE:</b> .X=±0.2 .XX=±0.15	繼德工業股份有限公司 Neltron Industrial Co., Ltd.	<b>DESCRIPTION:</b> D-SUB High Density Dip Straight Femlae	<b>SIZE</b> <b>A4</b>
D				<b>CHECKED:</b> JEREMY LIU				
C				<b>APPROVAL:</b> MIKE WU	<b>UNIT:</b> mm	<b>PART NO:</b> 5512-XXSA-01-BRJ C6F1		
B					<b>SCALE:</b>			<b>PROJECTION:</b>
A	03-Aug-2005	(PC0052)	CEL KING		<b>SHEET:</b> 1 / 1			
REV	DATE	FILE	BY					