



## Single-deck terminal block - Modular version - Pitch 5mm - 2÷3 poles

### GENERAL INFORMATION

pitch:	5 mm
housing height:	12,50 mm
housing depth:	9 mm
dimensional class:	medium
wire section:	2.5 mm <sup>2</sup> / 14 AWG
clamp opening size:	3 × 3 mm
wire stripping:	max 8 mm
operating temperature:	-40°C ÷ +105°C

### ELECTRICAL CHARACTERISTICS

current:	16A
voltage:	250V
test voltage:	2 kVrms/60s

### MECHANICAL CHARACTERISTICS

screw:	M3
max. torque:	0.5 Nm / 4.5 in.lbs

### APPROVALS DATA



current:  
voltage:  
FILE:

-  
-  
-

-  
-  
-

-  
-  
-

### MATERIALS

housing: PA - UL 94 V0

### AVAILABLE COLOURS



screw: Galvanized steel  
clamp/spring: Nickered copper alloy other colours: upon request  
terminal: Copper alloy

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
2	MVE162-5-V	N/A	N/A	N/A
3	MVE163-5-V	N/A	N/A	N/A
..	MVE16..-5-V	N/A	N/A	N/A