



Male plug-in connector - Side-by-side version - Pitch 7mm - 02 ÷ 12 poles

GENERAL INFORMATION

pitch:	7 mm
housing height:	9,20 mm
housing depth:	7.25 mm
dimensional class:	slow
wire section:	-
clamp opening size:	-
wire stripping:	-
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS

current:	8A
voltage:	500V
impulse voltage:	6 kV

MECHANICAL CHARACTERISTICS

APPROVALS DATA



current:	-	-	UL 1059
voltage:	-	-	8A factory / 8A field
FILE:	-	-	300V
			E178356

MATERIALS

AVAILABLE COLOURS

housing: PA - UL 94 V0
 screw: n/a
 clamp/spring: n/a
 terminal: Tin-plated copper alloy



other colours: upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
02	PV02-7-V	N/A	N/A	N/A
03	PV03-7-V	N/A	N/A	N/A
04	PV04-7-V	N/A	N/A	N/A
05	PV05-7-V	N/A	N/A	N/A
06	PV06-7-V	N/A	N/A	N/A
07	PV07-7-V	N/A	N/A	N/A
08	PV08-7-V	N/A	N/A	N/A
09	PV09-7-V	N/A	N/A	N/A
10	PV10-7-V	N/A	N/A	N/A
11	PV11-7-V	N/A	N/A	N/A
12	PV12-7-V	N/A	N/A	N/A