



Male plug-in connector - Vertical - Dual row - Pitch 5mm - 07/10/12/19 poles

GENERAL INFORMATION

pitch:	5 mm
housing height:	22,30 mm
housing depth:	28.6 mm
dimensional class:	medium
wire section:	-
clamp opening size:	-
wire stripping:	-
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS

current:	10A
voltage:	250V
impulse voltage:	4 kV

MECHANICAL CHARACTERISTICS

APPROVALS DATA



EN 61984

current:	12A
voltage:	250V
FILE:	CA02.04178



EN 61984

current:	12A
voltage:	250V
FILE:	40005779



UL 1059

current:	12A factory / 12A field
voltage:	300V
FILE:	E178356

MATERIALS

housing:	PA - UL 94 V0
screw:	n/a
clamp/spring:	n/a

AVAILABLE COLOURS



other colours: upon request

terminal:

Tin-plated copper alloy

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
07	PDV07-5	N/A	N/A	N/A
10	PDV10-5	N/A	N/A	N/A
12	PDV12-5	N/A	N/A	N/A
19	PDV19-5	N/A	N/A	N/A