



## Multi-deck terminal block - Modular version - Piani allineati - Pitch 10,16mm - 1÷2 poles

### GENERAL INFORMATION

pitch:	10,16 mm
housing height:	19,50 mm
housing depth:	22 mm
dimensional class:	medium
wire section:	2.5 mm <sup>2</sup> / 14 AWG
clamp opening size:	2.8 × 2.8 mm
wire stripping:	max 8 mm
operating temperature:	-40°C ÷ +130°C

### ELECTRICAL CHARACTERISTICS

current:	16A
voltage:	750V
test voltage:	3 kVrms/60s

### MECHANICAL CHARACTERISTICS

screw:	M3
max. torque:	0.5 Nm / 4.5 in.lbs

### APPROVALS DATA



EN 60998-1

current:	16A
voltage:	750V
wire section:	2.5mm <sup>2</sup>



EN 60998-1

16A
750V
2.5mm <sup>2</sup>



UL 1059

16A factory / 15A field
300V
14÷30AWG

torque:	0.5Nm	0.5Nm	4.5Lb-in
FILE:	EP149	40023956	E178356

### MATERIALS

housing:	PA - UL 94 V0
screw:	Galvanized steel
clamp/spring:	Nickel copper alloy
terminal:	Tin-plated copper alloy

### AVAILABLE COLOURS



other colours: upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
1	MVDK251-10,16-V	N/A	N/A	N/A
2	MVDK252-10,16-V	N/A	N/A	N/A
..	MVDK25..-10,16-V	N/A	N/A	N/A